

Product Spec Sheet

PROFILE OPTIONS

- Siding profiles for modern exterior cladding
- Soffit panels for rooflines and overhangs
- Architectural trims, fascia, and corner details
- Linear profiles for accent walls and contemporary façade elements
- Available in modern solid colors and realistic woodgrain finishes

KEY FEATURES

- Lightweight aluminum profiles for efficient handling and installation
- Fully integrated system: siding, soffit, trims, and linear profiles designed to work seamlessly together
- Concealed fastening system for a clean architectural appearance
- Durable finish engineered for superior fade and moisture resistance

APPLICATION

- Exterior cladding for residential, commercial, and institutional buildings
- Soffits, eaves, trims, fascia, and architectural details
- Accent walls and contemporary façade features
- Suitable for new construction, renovations, and façade upgrades

WARRANTY

- Comprehensive warranty covering material performance and finish durability
- Powder-coated and sublimated finishes guaranteed against fading, chalking, and peeling for fifteen (15) years from Substantial Completion
- Coverage applies to defects in materials and manufacturing under normal installation and use




www.VEDREX.ca

Info@VEDREX.ca


+1 416-300-1441

PROFILE SPECIFICATIONS


- 6" V-Groove:
 - Aluminum Alloy 6063-T6
 - 0.607 lb/ft
 - max length 19'




- 4" V-Groove:
 - Aluminum Alloy 6063-T6
 - 0.405 lb/ft
 - max length 19'



- 6" corrugated:
 - Aluminum Alloy 6063-T6
 - 0.573 lb/ft
 - max length 19'



- 2.5" V-Groove:
 - Aluminum Alloy 6063-T6
 - 0.327 lb/ft
 - max length 12'



TECHNICAL PERFORMANCE & CERTIFICATES

- Aluminum construction for long-term strength and dimensional stability
- Fire tested to Class A / CAN ULC S102, ASTM E84, ASTM E136, and CAN/CGSB 93.1 & 93.2
- Weather and moisture resistant, tested per ASTM E283, E330, and E331
- UV- and fade-resistant finishes certified to AAMA 2604/2605 and Qualicoat Class II & III
- Corrosion resistance tested to ISO 9227 and DIN EN salt spray standards
- Manufactured under ISO 9001 and IATF 16949 quality management systems
- Made from 100% recyclable aluminum with VOC- and solvent-free coatings; contributes to LEED and green building programs